

**Application:**

Construction Industry – General Industry – Municipalities

- to jet in wellpoints, wells or piles
- for the water supply at construction sites
- filling and testing of pipe lines
- cleaning construction vehicles and equipment
- fire fighting
- irrigation

Design:

HÜDIG high-pressure centrifugal pumps are multistaged, normal priming pumps, suitable for pumping clean or slightly dirty water without solid components. The pumps are driven by a Diesel engine. The pumps should be manually primed.

- mounted on single-axle trailer with pneumatic tyres suitable for construction-site-traffic (6 km/h)
- removable truck draw bar
- battery box and crane hook eye
- sturdy welded steel-tank-frame-chassis
- extra large capacity fuel tank

Pump:V_{max}: 60,0 m³/hp_{max}: 16,3 bar

Connection: suction side - 108 male –
discharge side - 50 male
4 stages

Engine:

Brand: DEUTZ

Type: F 3L1011F

Capacity: 32.5 kW

Speed: 2900 min⁻¹

Weight: 645 kg

Dimension: length: 1930 mm x width: 1360 mm x height: 1750 mm

Subject to change without prior notice!

HÜDIG - your partner to solve water problems.**HÜDIG**®

GmbH & Co. KG

Absenk- und Berechnungsanlagen

Heinrich-Hüdig-Straße 2 · 29227 Celle

Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18

e-mail: Info@huedig.de